NSN 5910-00-248-8508

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-248-8508

| view Offline at https://defobasegroup.com/nsi/0310-00-240-0300 |
|--|
| Body Style: |
| W/thd mtg hol (s)/stud(s), terminal(s) on one surface |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 3.875 inches |
| Body Width: |
| 1.375 inches |
| Body Height: |
| 1.375 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.972 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.972 inches |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Mounting Facility Type And Quantity: |
| 2 threaded mounting holes |
| Section Quantity: |
| 6 |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 0.300 microfarads all sections |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 80.0 degrees celsius |
| Thread Size: |
| 0.138 inches |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc all sections |
| Tolerance Range Per Section: |
| -10.00 to 25.00 percent 6th section |
| Case Material: |
| Metal |
| Terminal Surface Treatment: |
| Solder |

Mineral oil filled

Special Features:

Terminal Type And Quantity:

6 tab, solder lug

NSN 5910-00-248-8508

Paper Dielectric Fixed Capacitor - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0