## NSN 5910-00-248-8508

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-248-8508

view Offline at https://defobasegroup.com/nsi/0310-00-240-0300
Body Style:
W/thd mtg hol (s)/stud(s), terminal(s) on one surface
Reliability Indicator:
Not established
Body Length:
3.875 inches
Body Width:
1.375 inches
Body Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.972 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.972 inches
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting holes
Section Quantity:
6
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.300 microfarads all sections
Nonderated Operating Temp:
Between -55.0 degrees celsius and 80.0 degrees celsius
Thread Size:
0.138 inches
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc all sections
Tolerance Range Per Section:
-10.00 to 25.00 percent 6th section
Case Material:
Metal
Terminal Surface Treatment:
Solder

Mineral oil filled

**Special Features:** 

**Terminal Type And Quantity:** 

6 tab, solder lug

## NSN 5910-00-248-8508

Paper Dielectric Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0