

View Online at <https://aerobasegroup.com/nsn/5910-00-248-8987>

Body Style:

Rotary

Body Length:

1.312 inches

Body Width:

0.875 inches

Body Height:

0.433 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

650.0 all sections

Unthreaded Mounting Hole Diameter:

0.112 inches and 0.112 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.2

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Individual Section Quantity:

2

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encapsulated

Adjustment Device Rotation:

360.0 degrees clockwise

Adjustment Device Torque:

Between 4.000 inch-ounces and 24.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 threaded hole

Nonderated Operating Temp:

-55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.112 inches

Capacitance Range In Picofarads:

+7.0 to 45.0 all sections

Nonderated Voltage Rating And Type:

500.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

2 slotted screw

Capacitance Drift In Picofarads:

0.50 all sections

Special Features:

Mtg holes offset 0.156 in.C to c along lg

Material:

Ceramic base

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0