

View Online at https://aerobasegroup.com/nsn/5910-00-248-8998

Body Style:
Rotary
Body Length:
0.750 inches
Body Width:
0.938 inches
Body Height:
0.703 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
-650.0 single section
Unthreaded Mounting Hole Diameter:
0.112 inches and 0.112 inches
Dissipation Factor At 25 Deg Celsius In Percent:
0.2
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.656 inches
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encapsulated
Adjustment Device Rotation:
360.0 degrees clockwise
Insulation Dc Resistance At 25 Deg Celsius:
10000.0 megohms
Mounting Facility Type And Quantity:
2 threaded hole
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.112 inches
Capacitance Range In Picofarads:
+20.0 to 125.0 single section
Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.50 single section
Material:
Ceramic base
Terminal Type And Quantity:

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0