NSN 5910-00-249-1418

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-249-1418 **Body Style:** W/o mtg facilities, axial terminals Mil-std-1276 Wire Lead Type Designator: N-2 **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.322 inches **Body Length:** 0.813 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 500000.0 megohms **Capacitance Value Per Section:** 22000.000 picofarads single section **Nonderated Operating Temp:** Between -62.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 10000000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0450 **Terminal Surface Treatment:** Gold **Case Insulation Material:** Plastic **Precious Material And Location:** Terminal surface gold **Terminal Type And Quantity:** 2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-00-249-1418

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0