## NSN 5910-00-250-3150

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-250-3150 **Thread Class:** 2a **Body Style:** Piston **Bushing Diameter:** 0.253 inches **Bushing Length:** 0.250 inches **Body Length:** 0.625 inches **Overall Diameter:** 0.484 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.232 inches **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 

0.250 inches

**Capacitance Range In Picofarads:** 

+0.5/+3.0 single section

**Nonderated Voltage Rating And Type:** 

750.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

## NSN 5910-00-250-3150

Glass Dielectric Variable Capacitor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 1 wire lead                 |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |
| Fiig:                       |

A096a0