## NSN 5910-00-251-0866

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-251-0866
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.000 inches
Body Length:
0.375 inches
Body Width:
0.346 inches
Body Height:
0.106 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.270 inches and 0.330 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Insulation Resistance At Maximum Operating Temp:
100.0 megohm-microfarads
Capacitance Value Per Section:
4300.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
5000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.000
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyethylene terephthalate
Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-00-251-0866

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0