NSN 5910-00-252-9471

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-252-9471 **Body Style:** W/mtg bracket, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.750 inches **Body Length:** 2.125 inches **Body Width:** 0.750 inches **Body Height:** 1.188 inches **Terminal Diameter:** 0.040 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Inserted tab **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 60.0 megohm-microfarads **Capacitance Value Per Section:** 0.250 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material:** Metal

Insulation Resistance At Reference Temp:

6000.0 megohms

Terminal Surface Treatment:

Solder

NSN 5910-00-252-9471

Paper Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/2b government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0