NSN 5910-00-253-8288

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-253-8288 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.250 inches **Body Diameter:** 0.406 inches **Body Length:** 1.312 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 560.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Dc Leakage At Maximum Operating Temp: 24.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 6.000 microamperes **Terminal Surface Treatment:** Solder

Case Insulation Material: Plastic

NSN 5910-00-253-8288

Electrolytic Fixed Capacitor - Page 2 of 2



Test Data Document:

07690-429557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2	uninsu	latad	wire	heal
/	uninsu	area	wire	iean.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0