## NSN 5910-00-254-1188

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-254-1188               |
|---|
| Body Style:   |
| Rotary  |
| Body Diameter:  |
| 0.218 inches  |
| Body Height:  |
| 0.145 inches  |
| Center To Center Distance Between Terminals Parallel To Diameter:           |
| 0.195 inches  |
| Quality Factor At 25 Deg Celsius:   |
| 500.0   |
| Inclosure Type:   |
| Encased   |
| Adjustment Device Torque:   |
| Between 0.500 inch-ounces and 3.000 inch-ounces                             |
| Insulation Dc Resistance At 25 Deg Celsius:                                 |
| 10.0 gigohms  |
| Mounting Facility Type And Quantity:  |
| 2 terminal  |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 125.0 degrees celsius                     |
| Capacitance Range In Picofarads:  |
| +7.0 to 40.0 single section   |
| Nonderated Voltage Rating And Type:   |
| 25.0 dc continuous single section   |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| +0.00 to 14.00 and -14.00 to 5.00 single section                            |
| Adjustment Device Drive Type And Quantity:                                  |
| 1 slotted screw   |
| Capacitance Drift In Picofarads:  |
| 0.50 single section   |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A096a0  |