

View Online at https://aerobasegroup.com/nsn/5910-00-254-2234

#### **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.290 inches

#### **Body Length:**

0.156 inches

## Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.220 inches and 0.280 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

2.200 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

## **Tolerance Range Per Section:**

-0.10/+0.10 picofarads single section

#### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

# Quality Factor At Reference Temp:

1000.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-254-2234

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

