NSN 5910-00-254-2798

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-254-2798

Body Style:							
W/mtg tabs/flanges, terminal (s) on one surface							
Reliability Indicator:							
Not established							
Body Length:							
1.750 inches							
Body Width:							
0.790 inches							
Body Height:							
0.750 inches							
Continuous Current Rating In Amps:							
2.0							
Unthreaded Mounting Hole Diameter:							
0.144 inches							
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:							
2.188 inches							
Schematic Diagram Designator:							
No common or grounded electrode (s)							
Mounting Facility Type And Quantity:							
1 unthreaded mounting holes							
Features Provided:							
Hermetically sealed case							
Capacitance Value Per Section:							
1.500 microfarads single section							
Nonderated Operating Temp:							
Between -55.0 degrees celsius and 125.0 degrees celsius							
Nonderated Continuous Voltage Rating And Type Per Section:							
150.0 ac-rms single section							
Tolerance Range Per Section:							
-5.00/+5.00 percent single section							
Case Material:							
Metal							
Insulation Resistance At Reference Temp:							
500000.0 megohm-microfarads							
Dissipation Factor At Reference Tempurature In Percent:							
0.5000							
Terminal Surface Treatment:							
Solder							
Terminal Type And Quantity:							

N/a

2 tab, solder lug

Shelf Life:

NSN 5910-00-254-2798

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0