NSN 5910-00-254-7424

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-254-7424

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

2.250 inches

Body Diameter:

0.578 inches

Body Length:

0.765 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Impedance At Minimum Operating Tempurature In Ohms:

97.0

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

20.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

32.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

85.0 dc single section

Tolerance Range Per Section:

-15.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Tempurature In Percent:

9.0000

Equivalent Series Resistance At Reference Tempurature In Ohms:

6.30

Dc Leakage At Reference Temp:

8.000 microamperes

Terminal Surface Treatment:

Solder

NSN 5910-00-254-7424

Electrolytic Fixed Capacitor - Page 2 of 2



| Ī | erminal | Type | And | Quant | tity: |
|---|---------|------|-----|-------|-------|
| | | | | | |

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0