

View Online at <https://aerobasegroup.com/nsn/5910-00-255-3736>

Body Style:

W/o mtg facilities, radial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

1.100 inches

Body Length:

0.218 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.375 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Ticonderoga class cg (47), los angeles class ssn (688), sturgeon class ssn (637), virginia class cgn (41), spruance class dd (963), forrestal class cv. Hh-60h search and rescue helicopter. Hh-60j uscg search and rescue helicopter. Sh-60f asw carrier based helicopter.

Capacitance Value Per Section:

4700.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-22.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

4000.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0