

View Online at https://aerobasegroup.com/nsn/5910-00-256-5661

#### **Body Style:**

W/o mtg facilities terminal (s) on one surface

### Mil-std-1276 Wire Lead Type Designator:

N-1

**Reliability Indicator:** 

Not established

### Terminal Length:

1.250 inches

**Body Length:** 

2.000 inches

**Body Width:** 

2.000 inches

#### **Body Height:**

0.100 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

1000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

## **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### Case Material:

Ceramic

## Insulation Resistance At Reference Temp:

100000.0 megohms

## Dissipation Factor At Reference Tempurature In Percent:

0.1500

# **Terminal Surface Treatment:**

Solder

## Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0