Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-259-7934

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# Terminal Length:

2.000 inches

#### **Body Diameter:**

0.296 inches

#### **Body Length:**

1.000 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Plain foil

## Impedance At Minimum Operating Tempurature In Ohms:

357.0

## **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

5.600 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

15.0 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Aluminum

#### Dc Leakage At Reference Temp:

5.000 microamperes

## **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

## Terminal Type And Quantity:

2 uninsulated wire lead

#### Shelf Life:

N/a

# NSN 5910-00-259-7934

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0