## NSN 5910-00-259-7949



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-259-7949 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Length:** 0.230 inches **Body Width:** 0.335 inches **Body Height:** 0.230 inches Center To Center Distance Between Terminals Parallel To Length: 0.200 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 3.300 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 45.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.0000

Dc Leakage At Reference Temp:

3.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-259-7949

Electrolytic Fixed Capacitor - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0