

View Online at <https://aerobasegroup.com/nsn/5910-00-261-6536>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Body Diameter:

1.453 inches

Body Length:

2.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Xlos angeles class ssn (688), kidd class ddg, nimitz class cvn, forrestal class cv, oliver perry class ffg, ticonderoga class cg (47), spruance class dd (963), whidbey island class lsd. (agm-84) all-weather anti-ship harpoon missile.

Capacitance Value Per Section:

7500.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

15000.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dc Leakage At Reference Temp:

6000.000 microamperes

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0