

View Online at https://aerobasegroup.com/nsn/5910-00-264-6296

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

# Terminal Length:

Between 1.625 inches and 2.625 inches

### **Body Diameter:**

Between 0.589 inches and 0.609 inches

#### **Body Length:**

1.687 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Features Provided:

Hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

250.0 megohms

### **Capacitance Value Per Section:**

0.470 microfarads single section

# Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

25000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

**Terminal Surface Treatment:** 

Solder

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-19978/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

### Shelf Life:

N/a

Unit Of Measure:

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0