

View Online at https://aerobasegroup.com/nsn/5910-00-267-1767

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.1000

#### **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.344 inches

**Body Length:** 

0.937 inches

**Terminal Diameter:** 

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

### **Capacitance Value Per Section:**

0.220 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

# Test Data Document:

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-39022/1 government specification



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0