

View Online at https://aerobasegroup.com/nsn/5910-00-267-5347

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

## **Reliability Indicator:**

Established

# **Terminal Length:**

1.250 inches

### **Body Length:**

0.190 inches

#### **Body Width:**

0.190 inches

#### **Body Height:**

0.090 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

### **Capacitance Value Per Section:**

27.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

100000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

#### **Terminal Surface Treatment:**

Solder

#### **Test Data Document:**

81349-milc39014/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0