

View Online at https://aerobasegroup.com/nsn/5910-00-269-3655

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.750 inches

### **Body Diameter:**

0.359 inches

#### **Body Length:**

0.938 inches

#### **Terminal Diameter:**

0.020 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

### **Capacitance Value Per Section:**

5000.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

135.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

100000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

0.0270

## **Terminal Surface Treatment:**

Solder

## Case Insulation Material:

Plastic

## **Test Data Document:**

13499-933-1040-060 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0