## NSN 5910-00-269-3886

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-269-3886

Body	Styl	e:

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.400 inches

**Body Length:** 

0.833 inches

Body Width:

0.400 inches

Body Height:

0.400 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Mounting Facility Screw Thread Series Designator:** 

Unf

**Mounting Facility Type And Quantity:** 

1 threaded bushing

**Features Provided:** 

Mounting hardware and hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

150.0 megohms

**Capacitance Value Per Section:** 

47000.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.312 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

18000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

## NSN 5910-00-269-3886

Paper Dielectric Fixed Capacitor - Page 2 of 2



## **Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

_				
2	uninsi	ulatad	wiro	hoal

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0