

View Online at https://aerobasegroup.com/nsn/5910-00-269-4654

| Body Style: |
|---|
| Rotary |
| · |
| Terminal Length: 0.329 inches |
| |
| Overall Height: |
| 0.275 inches |
| Shaft Diameter: |
| 0.125 inches single shaft |
| Shaft Length: |
| 0.055 inches single shaft |
| Overall Diameter: |
| 0.375 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| 0.0 single section |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.500 inches |
| Quality Factor At 25 Deg Celsius: |
| 500.0 |
| Fragility Factor: |
| Moderately rugged |
| Terminal Width: |
| 0.093 inches |
| Terminal Thickness: |
| 0.012 inches |
| Inclosure Type: |
| Encapsulated |
| Adjustment Device Torque: |
| Between 1.000 inch-ounces and 6.000 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 1.0 gigohms |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +2.0 to 8.0 single section |
| Nonderated Voltage Rating And Type: |
| 350.0 dc continuous single section |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| -4.50 to 2.00 and -4.20 to 3.40 single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| |



Capacitance Drift In Picofarads:

0.50 single section

Material:

Ceramic inclosure

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0