NSN 5910-00-274-0127

Electrolytic Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/hsh/5910-00-274-0127 |
|--|
| Body Style: |
| W/o mtg facilities, terminal (s) on one end |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 2.008 inches |
| Body Length: |
| 3.125 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 6000.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 75.0 dc single section |
| Criticality Code Justification: |
| Zzzy |
| Tolerance Range Per Section: |
| -10.00/+100.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 0.032 |
| Dc Leakage At Reference Temp: |
| 6.000 microamperes |
| Case Insulation Material: |
| Plastic |
| Special Features: |
| Item must comply with requirements of defense supply center columbus production standard no. Lo1326 |
| Terminal Type And Quantity: |
| 2 threaded hole |
| Reference Number Differentiating Characteristics: |
| Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing |
| and testing specifications available at the dla icp |

Shelf Life:

N/a

NSN 5910-00-274-0127

Electrolytic Fixed Capacitor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0