NSN 5910-00-274-2855

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-274-2855 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.650 inches **Terminal Length:** 0.844 inches **Bushing Diameter:** 0.234 inches **Bushing Length:** 0.150 inches **Body Length:** 0.500 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -150.0/+150.0 single section **Terminal Diameter:** 0.025 inches **Quality Factor At 25 Deg Celsius:** 600.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 7.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:**

0.234 inches

Capacitance Range In Picofarads:

+2.0/+25.0 single section

NSN 5910-00-274-2855

Glass Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0