

View Online at https://aerobasegroup.com/nsn/5910-00-280-7573

### **Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.500 inches

### **Body Diameter:**

1.062 inches

#### **Body Length:**

2.312 inches

### **Unthreaded Mounting Hole Diameter:**

0.156 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Mounting Facility Type And Quantity:**

1 unthreaded mounting holes

### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

### Capacitance Value Per Section:

0.100 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

6000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

### **Terminal Surface Treatment:**

Solder

### **Case Insulation Material:**

Plastic

### **Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

Paper Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0