

View Online at https://aerobasegroup.com/nsn/5910-00-280-7578

### **Body Style:**

W/mtg bracket, axial terminals

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

1.000 inches

#### **Body Length:**

2.000 inches

### **Unthreaded Mounting Hole Diameter:**

0.156 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

### Mounting Facility Type And Quantity:

1 unthreaded mounting holes

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

#### **Capacitance Value Per Section:**

0.100 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

6000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

#### **Terminal Surface Treatment:**

Solder

#### **Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Paper Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0