Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-280-8222

Body Style:

W/mtg bracket, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.625 inches

Body Length:

1.375 inches

Body Width:

0.625 inches

Body Height:

1.063 inches

Terminal Diameter:

0.040 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Internal Electrical Connection Type:

Inserted tab

Mounting Facility Type And Quantity:

1 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

50000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

6000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Paper Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/2b government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0