## NSN 5910-00-280-8664

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-280-8664

| Body Style:  |  |  |  |  |
|--|--|--|--|--|
| W/thd mtg hol (s)/stud(s) terminal(s) on one surface                         |  |  |  |  |
| Reliability Indicator:   |  |  |  |  |
| Not established  |  |  |  |  |
| Body Length:   |  |  |  |  |
| 2.375 inches   |  |  |  |  |
| Body Width:  |  |  |  |  |
| 2.688 inches   |  |  |  |  |
| Body Height:   |  |  |  |  |
| 4.000 inches   |  |  |  |  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |  |  |  |  |
| 1.750 inches   |  |  |  |  |
| Schematic Diagram Designator:  |  |  |  |  |
| One terminal common to each section  |  |  |  |  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:  |  |  |  |  |
| 2.000 inches   |  |  |  |  |
| Mounting Facility Screw Thread Series Designator:                            |  |  |  |  |
| Unf  |  |  |  |  |
| Mounting Facility Type And Quantity:   |  |  |  |  |
| 4 threaded mounting studs  |  |  |  |  |
| Section Quantity:  |  |  |  |  |
| 2  |  |  |  |  |
| Features Provided:   |  |  |  |  |
| Hermetically sealed case   |  |  |  |  |
| Capacitance Value Per Section:   |  |  |  |  |
| 8.000 microfarads all sections   |  |  |  |  |
| Nonderated Operating Temp:   |  |  |  |  |
| Between -55.0 degrees celsius and 85.0 degrees celsius                       |  |  |  |  |
| Thread Size:   |  |  |  |  |
| 0.190 inches   |  |  |  |  |
| Nonderated Continuous Voltage Rating And Type Per Section:                   |  |  |  |  |
| 600.0 dc all sections  |  |  |  |  |
| Tolerance Range Per Section:   |  |  |  |  |
| -10.00 to 10.00 percent all sections   |  |  |  |  |
| Case Material:   |  |  |  |  |
| Metal  |  |  |  |  |
| Terminal Surface Treatment:  |  |  |  |  |
| Solder   |  |  |  |  |
| Terminal Type And Quantity:  |  |  |  |  |
| 3 tab, solder lug  |  |  |  |  |

N/a

Shelf Life:

## NSN 5910-00-280-8664

Paper Dielectric Fixed Capacitor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0