## NSN 5910-00-280-8725

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-280-8725

Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.250 inches
Body Length:
2.500 inches
Body Width:
1.188 inches
Body Height:
1.594 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 1.547 inches and 1.578 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.484 inches and 0.516 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.375 inches
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting holes
Section Quantity:
4
Features Provided:
Hermetically sealed case
Hermetically sealed case  Capacitance Value Per Section:
·
Capacitance Value Per Section:
Capacitance Value Per Section:  0.400 microfarads 4th section
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:  600.0 dc all sections
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:  600.0 dc all sections  Tolerance Range Per Section:
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:  600.0 dc all sections  Tolerance Range Per Section:  -20.00 to 10.00 percent all sections
Capacitance Value Per Section:  0.400 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:  600.0 dc all sections  Tolerance Range Per Section: -20.00 to 10.00 percent all sections  Case Material:

N/a

Shelf Life:

## NSN 5910-00-280-8725

Paper Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0