NSN 5910-00-283-5705

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5910-00-263-5705 |
|---|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.300 inches |
| Body Width: |
| 0.300 inches |
| Body Height: |
| 0.150 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.200 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 2200.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Quality Factor At Reference Temp: |
| 1000.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 5910-00-283-5705

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0