

View Online at https://aerobasegroup.com/nsn/5910-00-283-8067

Body Style:

Piston

Overall Length:

1.328 inches

Bushing Diameter:

0.190 inches

Bushing Length:

0.125 inches

Body Length:

0.922 inches

Overall Diameter:

0.312 inches

Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Quality Factor At 25 Deg Celsius:

350.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

100.0 gigohms

Bushing Width:

0.167 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

Capacitance Range In Picofarads:

+1.0/+52.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.02 single section



Test Data Document:

13499-922-3036 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0