NSN 5910-00-284-4720

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-284-4720 |
|---|
| Body Style: |
| Rotary |
| Terminal Length: |
| 0.360 inches |
| Body Length: |
| 0.750 inches |
| Body Width: |
| 0.531 inches |
| Body Height: |
| 0.234 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.312 inches |
| Terminal Width: |
| 0.093 inches |
| Terminal Thickness: |
| 0.012 inches |
| Inclosure Type: |
| Encapsulated |
| Adjustment Device Torque: |
| Between 2.000 inch-ounces and 8.000 inch-ounces |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +5.0 to 25.0 single section |
| Nonderated Voltage Rating And Type: |
| 350.0 dc continuous single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A096a0