

View Online at <https://aerobasegroup.com/nsn/5910-00-284-4796>

**Body Style:**

Rotary

**Body Length:**

1.300 inches

**Body Width:**

0.880 inches

**Body Height:**

0.406 inches

**Unthreaded Mounting Hole Diameter:**

0.145 inches and 0.145 inches

**Dissipation Factor At 25 Deg Celsius In Percent:**

0.2

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Individual Section Quantity:**

2

**Inclosure Type:**

Encapsulated

**Adjustment Device Torque:**

Between 4.000 inch-ounces and 24.000 inch-ounces

**Insulation Dc Resistance At 25 Deg Celsius:**

10.0 gigohms

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Capacitance Range In Picofarads:**

+7.0 to 45.0 all sections

**Nonderated Voltage Rating And Type:**

500.0 dc continuous all sections

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

+1.50 to 7.00 and -5.00/-1.50 all sections

**Adjustment Device Drive Type And Quantity:**

2 slotted screw

**Capacitance Drift In Picofarads:**

0.50 all sections

**Test Data Document:**

81349-mil-c-81 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 tab, solder lug

**Specification Data:**

81349-mil-c-81/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0