## NSN 5910-00-284-5027



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-284-5027 **Body Style:** W/thd bushing mtg, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 1.375 inches **Body Length:** 2.250 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 440.0 **Electrical Polarization:** Polarized **Mounting Facility Screw Thread Series Designator:** Un **Mounting Facility Type And Quantity:** 1 threaded bushing **Section Quantity:** 2 **Features Provided:** Mounting hardware **Capacitance Value Per Section:** 20.000 microfarads all sections **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.875 inches Nonderated Continuous Voltage Rating And Type Per Section: 350.0 dc all sections **Tolerance Range Per Section:** -10.00/+50.00 percent 2nd section **Case Material:** Metal **Capacitive Electrode Material:** 

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

12.0000

Dc Leakage At Reference Temp:

125.000 microamperes

## NSN 5910-00-284-5027

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0