NSN 5910-00-284-8877

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-284-8877 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 1.0000 **Terminal Length:** 1.625 inches **Body Diameter:** 0.188 inches **Body Length:** 0.688 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 50000.0 megohms **Capacitance Value Per Section:** 22000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 1000000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate **Test Data Document:** 81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-55514/1 government specification

Shelf Life:

N/a

NSN 5910-00-284-8877

Plastic Dielectric Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0