## NSN 5910-00-303-5314

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-303-5314

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
0.125 inches
Body Diameter:
0.188 inches
Body Length:
0.563 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
1 threaded mounting studs
Insulation Resistance At Maximum Operating Temp:
1000.0 megohms
Capacitance Value Per Section:
6.300 picofarads single section
6.300 picofarads single section  Nonderated Operating Temp:
Nonderated Operating Temp:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Range Per Section:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Range Per Section: -0.50/+0.50 picofarads single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Range Per Section: -0.50/+0.50 picofarads single section  Case Material:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Range Per Section: -0.50/+0.50 picofarads single section  Case Material:  Ceramic
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Range Per Section: -0.50/+0.50 picofarads single section  Case Material:  Ceramic  Quality Factor At Reference Temp:
Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.099 inches Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Range Per Section: -0.50/+0.50 picofarads single section Case Material: Ceramic Quality Factor At Reference Temp: 1000.0000
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.099 inches  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Range Per Section: -0.50/+0.50 picofarads single section  Case Material: Ceramic  Quality Factor At Reference Temp: 1000.0000  Terminal Surface Treatment:

N/a

Shelf Life:

## NSN 5910-00-303-5314

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0