NSN 5910-00-307-4325

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-307-4325 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.203 inches **Body Length:** 0.515 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 1090.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 1.700 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 2.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section **Tolerance Range Per Section:** -15.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 1.000 microamperes **Terminal Surface Treatment:** Solder

Case Insulation Material:

Plastic

NSN 5910-00-307-4325

Electrolytic Fixed Capacitor - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0