# NSN 5910-00-309-2146

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-309-2146

## **Body Style:**

W/thd bushing mtg, terminals on opposite ends

# **Reliability Indicator:**

Not established

# **Terminal Length:**

2.250 inches

## **Body Diameter:**

0.375 inches

#### **Body Length:**

0.766 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

# Anode Type:

Solid

## Impedance At Minimum Operating Tempurature In Ohms:

93.0

## **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

25.000 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

12.5 microamperes

# Nonderated Continuous Voltage Rating And Type Per Section:

125.0 dc single section

# **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

## **Case Material:**

Metal

# **Capacitive Electrode Material:**

Tantalum

# Equivalent Series Resistance At Reference Tempurature In Ohms:

10.00

# Dc Leakage At Reference Temp:

2.000 microamperes

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5910-00-309-2146

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0