Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-320-8302

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.228 inches

#### **Body Length:**

0.590 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

#### Impedance At Minimum Operating Tempurature In Ohms:

# 200.0

**Electrical Polarization:** 

Polarized

# **Capacitance Value Per Section:**

11.000 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

24.0 microamperes

# Nonderated Continuous Voltage Rating And Type Per Section:

60.0 dc single section

# **Tolerance Range Per Section:**

-15.00/+75.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Tantalum

# Equivalent Series Resistance At Reference Tempurature In Ohms:

6.00

#### Dc Leakage At Reference Temp:

6.000 microamperes

## **Terminal Surface Treatment:**

Solder

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

# NSN 5910-00-320-8302

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0