

View Online at <https://aerobasegroup.com/nsn/5910-00-321-8296>

Thread Class:

2a

Bushing Diameter:

0.469 inches

Bushing Length:

0.438 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.001

Mounting Facility Screw Thread Series Designator:

Un

Inclosure Type:

Hermetically sealed

Adjustment Device Rotation:

3.0 turns counterclockwise

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

100.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.469 inches

Capacitance Range In Picofarads:

+1150.0/+2605.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-3.00/+3.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0