Mica Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-321-8296

Thread Class:
2a Rushing Diamatan
Bushing Diameter: 0.469 inches
Bushing Length:
0.438 inches
Dissipation Factor At 25 Deg Celsius In Percent:
0.001
Mounting Facility Screw Thread Series Designator:
Un
Inclosure Type:
Hermetically sealed
Adjustment Device Rotation:
3.0 turns counterclockwise
Bushing Shape:
Round
Insulation Dc Resistance At 25 Deg Celsius:
100.0 gigohms
Mounting Facility Type And Quantity:
1 threaded bushing
Thready Qty Per Inch (tpi):
32
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.469 inches
Capacitance Range In Picofarads:
+1150.0/+2605.0 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius:
-3.00/+3.00 single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5910-00-321-8296

Mica Dielectric Variable Capacitor - Page 2 of 2

Fiig: A096a0

