## NSN 5910-00-325-8226

W/thd bushing mtg, terminals on opposite end

**Body Style:** 

Reliability Indicator:

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-325-8226

| Not established   |
|---|
| Width Across Flats:   |
| 0.375 inches  |
| Terminal Length:  |
| 0.437 inches  |
| Body Length:  |
| 0.875 inches  |
| Terminal Diameter:  |
| 0.051 inches  |
| Schematic Diagram Designator:   |
| Feedthrough   |
| Mounting Facility Screw Thread Series Designator:                     |
| Unf   |
| Mounting Facility Type And Quantity:                                  |
| 1 threaded bushing  |
| Capacitance Value Per Section:  |
| 200.000 picofarads single section                                     |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -22.0/+22.0 without voltage applied single section                    |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 85.0 degrees celsius                |
| Thread Size:  |
| 0.312 inches  |
| Nonderated Continuous Voltage Rating And Type Per Section:            |
| 2000.0 dc single section  |
| Tolerance Range Per Section:  |
| -20.00/+20.00 percent single section                                  |
| Case Material:  |
| Metal   |
| Insulation Resistance At Reference Temp:                              |
| 10000.0 megohms   |
| Dissipation Factor At Reference Tempurature In Percent:               |
| 1.5000  |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |

N/a

Shelf Life:

## NSN 5910-00-325-8226

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A010b0