

View Online at <https://aerobasegroup.com/nsn/5910-00-327-0983>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

1.000 inches

**Body Length:**

0.400 inches

**Body Width:**

0.360 inches

**Body Height:**

0.095 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.225 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:**

10000.0 megohms

**Capacitance Value Per Section:**

91.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Temperature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:**

+0.0 to 70.0 single section

**Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.0007

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-milc39001 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0