NSN 5910-00-327-8609

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-327-8609 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established **Terminal Length:** 1.250 inches **Body Length:** 0.300 inches **Body Width:** 0.300 inches **Body Height:** 0.100 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.185 inches and 0.215 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 0.120 microfarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -25.0/+15.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.5000 **Terminal Surface Treatment:** Solder **Test Data Document:**

83298-1548241 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 insulated wire lead w/terminal lug

Shelf Life:

N/a

NSN 5910-00-327-8609

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0