NSN 5910-00-329-5749

Glass Dielectric Variable Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-329-5749
Body Style:
Piston
Overall Length:
0.732 inches
Body Length:
0.577 inches
Overall Diameter:
0.312 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.440 inches
Center To Center Distance Between Terminals Parallel To Diameter:
Between 0.235 inches and 0.281 inches
Quality Factor At 25 Deg Celsius:
650.0
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 6.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
1000.0 kilohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Capacitance Range In Picofarads:
+0.8/+8.5 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0