

View Online at https://aerobasegroup.com/nsn/5910-00-329-5938

| Body Style: |
|--|
| Compression |
| Body Length: |
| 0.210 inches |
| Body Width: |
| 0.210 inches |
| Body Height: |
| 0.060 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| 50.0 single section |
| Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: |
| -50.0 to 50.0 single section |
| Quality Factor At 25 Deg Celsius: |
| 3000.0 |
| Inclosure Type: |
| Encapsulated |
| Adjustment Device Torque: |
| Between 0.100 inch-ounces and 1.000 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 10000.0 megohms |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +1.0 to 4.5 single section |
| Nonderated Voltage Rating And Type: |
| 250.0 dc continuous single section |
| Adjustment Device Drive Type And Quantity: |
| 1 square hole |
| Terminal Type And Quantity: |
| 2 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A096a0 |
| |