## NSN 5910-00-329-7175

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-329-7175 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.395 inches **Body Length:** 2.719 inches **Terminal Diameter:** Between 0.030 inches and 0.040 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 54.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 56.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 30.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 10.0000 Dc Leakage At Reference Temp: 10.000 microamperes **Terminal Surface Treatment:** Solder

**Case Insulation Material:** 

**Plastic** 

## NSN 5910-00-329-7175

Electrolytic Fixed Capacitor - Page 2 of 2



| Terminal Type Ar | nd Quantity: |
|------------------|--------------|
|------------------|--------------|

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0