

View Online at https://aerobasegroup.com/nsn/5910-00-331-9674

| Pody Style |
|--|
| Body Style: |
| Chip type |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 0.110 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.110 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 270.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 90.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Glass |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Quality Factor At Reference Temp: |
| 10000.0000 |
| Terminal Type And Quantity: |
| 2 bonding pad |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5910-00-331-9674 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

